

Acu-Gas HDPE Pipe is the product of choice for below-ground natural gas, LP gas mains and distribution pipelines. It is approved under AS 5601-2004: Gas Installations.

This lightweight product can offer project efficiency as it is easy to transport, handle and install.

Its integrity and durability is proven in the field by utilities Australia wide. Its flexibility can accommodate minor changes in direction and ground movement.

Acu-Tech can also provide a large range of fittings and ancillaries that are specified and listed in the ATCO and APA Gas Materials Catalogue.

PRODUCT CODE	OUTSIDE DIAMETER (mm)	INSIDE DIAMETER (mm)	SDR RATING	NOMINAL PRESSURE RATING IN BAR (DESIGN SAFETY FACTOR - 2) <sup>1</sup>	AVAILABLE LENGTHS (m)
PYS01611100APA	16***	9.8	11	10	100m Coil
PYS02011100APA	20***	13.8	11	10	100m, 200m Coil
	20***	15.0	17	6	100m, 200m Coil
PYS03211050APA	25***	20.0	17	6	100m, 200m Coil
	25***	18.0	11	10	100m Coil
	32***	25.8	11	10	50m, 100m Coil
	40	32.3	11	10	6m Length
PYS04011150APA	40	32.3	11	10	100m Coil
	50***	40.4	11	10	100m Coil
PYS063110007APA	63	51.0	11	10	6m,7m Length
PYS06311050APA	63	51.0	11	10	50m, 100m Coil
	90***	78.9	17	6	6m, 50m, 100m Coil
PYS09011007APA	90***	73.1	11	10	7m, 12m, 100m Coil
	110	96.4	17	6	6m, 12m Length
	110	96.4	17	6	50m, 100m Coil
PYS11011006APA	110	89.3	11	10	6m, 12m Length*
PYS12511012APA	125***	101.5	11	10	12m Length
	160	140.6	17	6	6m, 12m Length
	160	129.9	11	10	6m, 12m Length*
	225	197.6	17	6	6m, 12m Length
	225	182.7	11	10	6m, 12m Length*
	280***	227.8	11	10	12m Length

<sup>\*</sup> Non-Standard item, please contact Acu-Tech for availability. | \*\*\* Products are state-specific, contact sales for more information.